



Description

IP Intercom unit HT8005

Model

Hessing's **Ethernet/IP Intercoms** and IP intercom solutions deliver fast direct one button communication over TCP/IP networks. The patented technology is able to deliver speech quality audio over LAN and WAN networks using a minimum of network bandwidth.. The IP intercom unit is a stand alone unit providing the connection between the customer and operator.

Functionality

The IP intercom unit is a boxed unit 90 x 100 x 35 mm mountable on a rail, with only a speaker (functioning as microphone and speaker) and a push button connected the intercom is complete. The customer pushes the intercom button receives a attention signal so they know that their call is processed. On the operator side a attention signal alerts the operator of a incoming call. The operator answers the call by opening the corresponding intercom path.

Specifications

- High quality audio over Ethernet.
- Call button.
- Easy scalability (ability to expand the number of intercoms and main units)
- Seamless integration in HT 5000 communication systems

- Dimensions : 90 x 100 x 35 mm (w x h x d), easy to mount on a rail.
- Display type: Active matrix TFT LCD met touch screen
- Speaker : 8 ohm / 3 W
- Network interface: 10/100 Base-T Ethernet (auto detect) RJ45
- IP Adres: Fixed
- Transport bandwidth : 80 kbps per TCP/IP session
- Audio resolutie: PCM-8 en μ LAW-16 bit
- Audio sample rate: 8 kHz